


Stainless Steel Single-Row Angular Contact Ball Bearing



select	Inquiry	Bearing No.	d(mm)	D(mm)	B(mm)	Dynamic Load Rating(KN)	Static Load Rating(KN)	Speed Limit(r/min) (Grease)	Speed Limit(r/min) (Oil)	Weight(kg)
S7000	10	26	8	5	2.35	34000	42000	0.021		
AC										
S7001	12	28	8	5.4	2.75	29000	37000	0.024		
AC										
S7002	15	32	9	6.1	2.45	26000	32000	0.035		
AC										
S7003	17	35	10	6.75	4.15	23000	28000	0.045		
AC										
S7004	20	42	12	10.3	6.1	19000	24000	0.079		
AC										
S7005	25	47	12	11.3	7.4	17000	21000	0.091		
AC										
S7006	30	55	13	14.5	10.1	14000	18000	0.133		
AC										
S7007	35	62	14	17.5	12.6	12000	15000	0.17		
AC										
S7008	40	68	15	18.7	14.6	11000	14000	0.21		
AC										
S7009	45	75	16	22.2	17.7	10000	12000	0.26		
AC										
S7010	50	80	16	23.6	20.1	9200	11000	0.029		
AC										
S7000	10	26	8	4.65	2.15	25000	33000	0.021		
B										
S7001	12	28	8	4.95	2.5	22000	29000	0.024		
B										
S7002	15	32	9	5.55	3.15	19000	25000	0.035		
B										
S7003	17	35	10	6.1	3.75	17000	23000	0.045		
B										
S7004	20	42	12	9.35	5.55	14000	19000	0.079		
B										

Stainless Steel Single-Row Angular Contact Ball Bearing

S7005 B	25	47	12	11.3	7.4	13000	17000	0.091
S7006 B	30	55	13	13.1	9.2	11000	14000	0.133
S7007 B	35	62	14	15.8	11.4	9200	12000	0.17
S7008 B	40	68	15	16.8	13.2	8300	11000	0.21
S7009 B	45	75	16	20	16	7500	10000	0.26
S7010 B	50	80	16	21.2	18.1	6900	9200	0.029