


# Stainless Steel Double-Row Angular Contact Ball Bearing



select	Inquiry	Bearing No.	d(mm)	D(mm)	B(mm)	Dynamic Load Rating(KN)	Static Load Rating(KN)	Speed Limit(r/min) (Grease)	Speed Limit(r/min) (Oil)	Weight(kg)
S42002RS	10	30	14	9.23	5.2	18000	22000	0.049		
S42012RS	12	32	14	10.6	6.2	17000	20000	0.053		
S42022RS	15	35	14	11.9	7.5	14000	17000	0.059		
S42032RS	17	40	16	14.8	9.5	12000	15000	0.09		
S42042RS	20	47	18	17.8	12.5	10000	13000	0.14		
S42052RS	25	52	18	19	14.6	9000	11000	0.16		
S42062RS	30	62	20	26	20.8	8000	9500	0.26		
S42072RS	35	72	23	35.1	28.5	6700	8000	0.4		
S42082RS	40	80	23	37.1	32.5	6000	7000	0.5		
S42092RS	45	85	23	39	36	5600	6700	0.54		
S42102RS	50	90	23	41	40	5000	6000	0.58		
S52002RS	10	30	14	6.95	3.8	14000	19000	0.049		
S52012RS	12	32	15.9	9.15	5.05	13000	17000	0.057		
S52022RS	15	35	15.9	10	6.05	11000	15000	0.064		
S52032RS	17	40	17.5	13.2	8.15	10000	14000	0.091		
S52042RS	20	47	20.6	19.7	12.6	8800	12000	0.12		
S52052RS	25	52	20.6	21.4	14.8	7700	10000	0.19		
S52062RS	30	62	23.8	29.7	21.3	6400	8600	0.029		
S52072RS	35	72	26.7	39.2	29	5500	7300	0.43		
S52082RS	40	80	30.2	44.4	33.6	5000	6700	0.57		
S52092RS	45	85	30.2	49.9	38.4	4600	6100	0.62		
S52102RS	50	90	30.2	53.3	43	4300	5600	0.67		
S52112RS	55	100	33.3	65.9	55.2	3800	5100	0.96		
S53012RS	12	37	19	15.3	9.15	11000	14000	0.11		
S53022RS	15	42	19	17.2	10.1	9900	13000	0.132		

## Stainless Steel Double-Row Angular Contact Ball Bearing

---

S53032RS	17	47	22.2	20.4	$\frac{12.}{10}$	9000	12000	0.181
S53042RS	20	52	22.2	20.6	12.7	8000	11000	0.217
S53052RS	25	62	25.4	30.5	20.5	6700	8900	0.372
S53062RS	30	72	30.2	39.5	27.5	5700	7600	0.553
S53072RS	35	80	34.9	49.5	35	5000	6600	0.766