


7300C Series



| select | Inquiry | Bearing No. | Boundary dimensions [mm] | | | Basic load ratings(kN) | | Limiting speed(rpm) | | Mass Kg |
|--------|---------|-------------|-----------------------------|-------|-------|------------------------|-------------|----------------------|-----|------------|
| | | | d | D | B | Dynamic(Cr) | Static(Cor) | Grease | Oil | |
| 7300C | 10 | 35 | 11 | 9.8 | 4.6 | 18000 | 26000 | 0.053 | | |
| 7301C | 12 | 37 | 12 | 11.8 | 5.6 | 17000 | 24000 | 0.06 | | |
| 7302C | 15 | 42 | 13 | 13.2 | 6.7 | 15000 | 21000 | 0.084 | | |
| 7303C | 17 | 47 | 14 | 15.7 | 8.2 | 13000 | 19000 | 0.16 | | |
| 7304C | 20 | 52 | 15 | 18.4 | 9.8 | 12000 | 17000 | 0.15 | | |
| 7305C | 25 | 62 | 17 | 27.8 | 15.9 | 9500 | 14000 | 0.23 | | |
| 7306C | 30 | 72 | 19 | 33.2 | 21.2 | 8500 | 12000 | 0.35 | | |
| 7307C | 35 | 80 | 21 | 40.3 | 25.8 | 7500 | 10000 | 0.47 | | |
| 7308C | 40 | 90 | 23 | 49.3 | 32.3 | 6700 | 9000 | 0.66 | | |
| 7309C | 45 | 100 | 25 | 63.1 | 42.9 | 6000 | 8000 | 0.86 | | |
| 7310C | 50 | 110 | 27 | 74.9 | 50.9 | 5600 | 7500 | 1.08 | | |
| 7311C | 55 | 120 | 29 | 86.4 | 59.5 | 5000 | 6700 | 1.42 | | |
| 7312C | 60 | 130 | 31 | 98.6 | 68.5 | 4800 | 6300 | 1.71 | | |
| 7313C | 65 | 140 | 33 | 113.1 | 79.6 | 4300 | 5600 | 2.23 | | |
| 7314C | 70 | 150 | 35 | 126 | 91.6 | 4000 | 5300 | 2.67 | | |
| 7315C | 75 | 160 | 37 | 140.7 | 103.9 | 3800 | 5000 | 3.1 | | |
| 7316C | 80 | 170 | 39 | 156.1 | 112.2 | 3600 | 4800 | 3.6 | | |
| 7317C | 85 | 180 | 41 | 160.7 | 130.5 | 3400 | 4500 | 4.38 | | |
| 7318C | 90 | 190 | 43 | 184.9 | 159.9 | 3200 | 4300 | 5.6 | | |
| 7319C | 95 | 200 | 45 | 201.1 | 179.8 | 3200 | 4200 | 6.6 | | |

7300C Series

| | | | | | | | | |
|-------|-----|-----|----|-------|-------|------|------|------|
| 7320C | 100 | 215 | 47 | 222.1 | 206.7 | 3000 | 4000 | 7.58 |
| 7321C | 105 | 225 | 49 | 235.8 | 225.6 | 2800 | 3800 | 8.85 |
| 7322C | 110 | 240 | 50 | 263.2 | 261.9 | 2600 | 3600 | 10.5 |